

KCC 4770 (K-C 17,310)
PATENTAMENDMENTS TO THE CLAIMS

This listing will replace all prior versions, and listings, of claims in the application, including the listing provided in Amendment B.

Listing of Claims:

1. (canceled).

2. (withdrawn) The mechanical fastening system of claim 1 wherein the first fastening component has been stabilized by laminating the oriented nonwoven loop material to an elastomeric material to provide elastic properties to the resulting composite.

3. (currently amended) The mechanical fastening system of claim ~~1~~ 28 wherein the nonwoven web has a machine direction and a cross-machine direction, the constituent fibers direction of extension of the nonwoven web are oriented being in the machine direction of said nonwoven web.

4. (withdrawn) The mechanical fastening system of claim 1 wherein the constituent fibers of the nonwoven web are oriented in the cross machine direction.

5. (withdrawn) The mechanical fastening system of claim 1 wherein the first fastening component has been stabilized by thermally treating the material.

6. (canceled).

7. (canceled).

KCC 4770 (K-C 17,310)
PATENT

8. (withdrawn) The mechanical fastening system of claim 6 wherein constituent fibers of the nonwoven web become oriented in the direction of the force with concomitant necking or narrowing of the nonwoven web in the direction perpendicular to the applied force.

5-11-04
9. (currently amended) The mechanical fastening system set forth in ~~of~~ claim 6 ~~28~~ wherein the nonwoven web ~~is formed~~ of comprises substantially continuous fibers.

10. (canceled).

11. (withdrawn) The mechanical fastening system of claim 6 wherein constituent fibers of the nonwoven web are oriented in the cross machine direction.

12. (canceled).

13. (canceled).

14. (withdrawn) The disposable absorbent article of claim 12 wherein the first fastening component has been stabilized by laminating the oriented nonwoven loop material to an elastomeric material to provide elastic properties to the resulting composite.

15. (canceled).

16. (withdrawn) The disposable absorbent article of claim 15 wherein the first fastening component has been stabilized by laminating the oriented nonwoven loop material to an elastomeric material to provide elastic properties to the resulting composite.

17. (withdrawn) The disposable absorbent article of claim 15 wherein the first fastening component has been

KCC 4770 (K-C 17,310)
PATENT

produced by orienting the nonwoven web in the machine direction and necking the nonwoven web in the cross machine direction.

18. (canceled).

19. (canceled).

20. (withdrawn) A disposable absorbent article of claim 15 wherein constituent fibers of the nonwoven web become oriented in the direction of the force with concomitant necking or narrowing of the nonwoven web in the direction perpendicular to the applied force.

21. (withdrawn) The disposable absorbent article of claim 15 wherein the first fastening component has been stabilized by thermally treating the material.

22-27. (previously canceled).

28. (New) A mechanical fastening system for an article, said fastening system comprising:

a first fastening component comprising an oriented nonwoven loop material secured to a substrate, the oriented nonwoven loop material comprising a nonwoven web of fibers, said web being extensible from a relaxed configuration to an extended configuration wherein in the extended configuration a greater number of fibers of the nonwoven web are oriented in the direction in which the web is extended than in the relaxed configuration of the web, the web being in its extended configuration on the substrate; and

a second fastening component comprising a hook material, the oriented nonwoven loop material of the first fastening component being adapted for releasable connection with the hook material of the second fastening component.

KCC 4770 (K-C 17,310)
PATENT

29. (New) The mechanical fastening system set forth in claim 28 wherein the nonwoven web is generally free from substantial necking and gathering in a direction perpendicular to the direction in which the web is extended.

30. (New) The mechanical fastening system set forth in claim 28 in combination with the article, said substrate being formed integrally with the article.

31. (New) The mechanical fastening system set forth in claim 28 wherein the substrate is substantially inelastic.

32. (New) The mechanical fastening system set forth in claim 29 wherein the substrate is substantially inelastic.

33. (New) An absorbent article for personal wear, the absorbent article comprising:

a liquid permeable inner layer for contact with the wearer's skin, an outer layer in superposed relationship with the inner layer, and an absorbent layer disposed between the inner layer and the outer layer, the article having a first end region and a second end region; and

a mechanical fastening system comprising at least one first fastening component disposed generally at the first end region of the article and at least one second fastening component disposed generally at the second end region of said article and adapted for releasable connection with the at least one first fastening component to secure the article on a wearer of said article, the at least one first fastening component comprising an oriented nonwoven loop material secured to a substrate, the oriented nonwoven loop material comprising a nonwoven web of fibers, said web being extensible from a

KCC 4770 (K-C 17,310)
PATENT

relaxed configuration to an extended configuration wherein in
the extended configuration a greater number of fibers of the
20 nonwoven web are oriented in the direction in which the web is
extended than in the relaxed configuration of the web, said web
being in its extended configuration on the substrate, the at
least one second fastening component comprising a hook
material, the oriented nonwoven loop material of the at least
25 one first fastening component being adapted for releasable
connection with the hook material of the at least one second
fastening component.

34. (New) The absorbent article set forth in claim 33
wherein the nonwoven web is generally free from substantial
necking and gathering in a direction perpendicular to the
direction in which the web is extended.

35. (New) The absorbent article set forth in claim 33 in
combination with the article wherein the substrate is formed
integrally with the article.

36. (New) The absorbent article set forth in claim 33
wherein the substrate is substantially inelastic.

37. (New) The absorbent article set forth in claim 33
wherein the nonwoven web of the at least one first fastening
component has a machine direction and a cross-machine
direction, the direction in which the web is extended being the
5 machine direction.

38. (New) A mechanical fastening system for an article,
said fastening system comprising:

a first fastening component comprising an oriented
nonwoven loop material free from attachment to a backing

KCC 4770 (K-C 17,310)
PATENT

5 substrate, the oriented nonwoven loop material comprising a
nonwoven web of fibers, said web being extensible from a
relaxed configuration to an extended configuration wherein in
the extended configuration a greater number of fibers of the
nonwoven web are oriented in the direction in which the web is
10 extended than in the relaxed configuration of the web, said web
being in its extended configuration; and

15 a second fastening component comprising a hook material,
the oriented nonwoven loop material of the first fastening
component being adapted for releasable connection with the hook
material of the second fastening component.

39. (New) The mechanical fastening system set forth in
claim 38 in combination with the article, the first fastening
component defining at least a portion of said article.